See Instructions on back of page 6.

State of California—Environmental Protection Agency

Department of Toxic Substances Control

793)

Yellow: GENERATOR RETAINS

SAFETY-KLEEN CORP. (DESIGNATED FACILITY)

Generator Company: DOUGLAS AIRCRAFT

EPA ID NO	C4T000613976	
	(DESIGNATED FACILITY)	

ADDRESS: 2120 SOUTH VALE ST SANTA ANA DATE CA 92704 Under manifest / sales service number be restricted under 40 CFR Part 268. In accordance with 40 CFR Part 268.7, the generator noted below is shipping to you a waste determine be restricted under 40 CFR Part 268. In accordance with 40 CFR Part 268.7, the generator hereby provides notice that the waste is restricted from land A copy of this form must be kept by the generator and facility for five (5) years from the date of waste shipment. WASTE NAME (FOR NON-WASTE WATER) Waste Petroleum Naphtha 105 D001, Ignitable Liquid (High TOC Subcategory) Lead Benzene Methyl Ethyl Ketone D008, D008, D008, D008, D009, Tetrachloroethylene D001, D006, D008,	disposal.) (FSUBS) (ste water)
A copy of this form must be kept by the generator and facility for five (5) years from the date of waste snipment. WASTE NAME (FOR NON-WASTE WATER) (FOR NON-WASTE WATER) WASTE THE WASTE MAY CONTAIN THE FOLLOWING RESTRICTED CONSTITUENTS DO01, Ignitable Liquid (High TOC Subcategory) Halogenated Organic Compounds (HOC's) ≥ 1000 mg/l Cadmium Lead D018, D035, D039, D040, Tetrachloroethylene Tetrachloroethylene Todamium Tetrachloroethylene Trichloroethylene Trichloroethylene Naphtha 140 D001, D006, D008, D009, D0) (FSUBS) ste water)
Usaste Petroleum Naphtha 105 Doo6, Doo8, Doo8, Doo35, Doo4, Doo4, Doo6, Doo8, Doo9, Doo4, Doo8, Doo8, Doo9, Doo4, Doo8, Doo9, Doo4, Doo8, Doo9, Doo4, Doo9, Doo9	ste water)
H E Waste Petroleum Naphtha 140 D006, D008, D018, D018, D039, D039, D039, D039, D04 Cadmium Lead Benzene Not Established Not Established Not Established	
P	aste water
P Cyclonic, D008, D018, D018, D039, D040, Solvent OR Actrel Solvent (If customer specific TCLP is not available) D006, D008, D008, D008, D008, D008, D008, D008, D008, D008, D009, D040, Solvent (If customer specific TCLP is not available) D006, D008,	
T T T T T T T T T T T T T T T T T T T	
X E S Waste Compound Cleaning Liquid/ Immersion cleaner 699 Waste Compound Cleaning Liquid/ Immersion cleaner 699 HOC's ≥ 1000 mg/l Cadmium 1.0 (non-waste water) 5.0 (non-waste Water Not Established	iter)
MACHINE SPECIFIC EXCESS FLUID IN DRUM? OFF - COLOR? MORE THAN 30% UNUSUAL UNUSUAL NINCLUDED/A	
P	
S T A T T T T T T T T T T T T T T T T T	
SPECIFIC GRAVITY ACCEPTANCE GUIDELINES 1-088-05-1187 14 094268 9430 The constituent composition is based on knowledge of the waste (via Material Safety Data Sheets for the chemical(s) used, and the process which created the waste). *These treatment standards do not preclude reclamation prior to final disposition.	

Safety-Kleen Corp. manages the above waste through its recycling and fuels programs in accordance with all applicable elements of the land disposal restrictions.

BOE-C6-0207190

CAD086510005

printed on recycled pa

UST

0

1

2

3

8

10

11 12

CONSUMER REFERENCE INFO (NUMERIC ONLY)

1000 North Randall Road Elgin, Illinois 60123-7857

FOR SERVICE CALL TRANSPORTER

BILL THIEBERT

DUNS NO. 05106-0408 FED. ID NO. 39-6090019

SCHED		SCHEDULED SERVICE TERRITORY		HENCE IBER	
3 A	72.57	1 6	0.00 h	Jan. S	à

4	P		*	come.	0	Si.	8-	0	5	-485	1	, and		7-	9			
	۵	Q	1,5	6,0	Ĺ.	A	S	4	I	R		R	A	FT				
	4	1	200	N		, i	OE		6.		0	E	10	1	7	*	60	Guna J

714-435-1862

714-435-0605

2200+ CA LOR REQ*D

MANIFEST NUMBER

CUSTOMER

19503 S NORMANDIE

714-435-9206

O TORRANCE SERVICE DATE SALESMEN'S NO. SALES TAX EXEMPTION NUMBER OVER 80 DAYS CODE - 94 2266.61 37-2-4 05-095-8937 CHAIN **CUSTOMER P.O. NUMBER** GENERATOR'S/CUSTOMER PHONE # O.C. SVC P/S PROD. P/S SERVICE TAX C.O.M.S. TAX PRODUCT TAX <u> 310-533-6686</u> 923 0825 001 .0825 0029 SERVICE TOTAL SERVICE SERVICE NO. **SERIAL NO** SCHEDULED DATE SERVICE TERM REMARKS TAX TERM 0.357 CHARGE CHARGE 40-00192 94 OR OR & C 1711 1 96 08 OR OR ECT OR DR OR PUL ECT 図 TOTAL DECALS IN PLACE AND LEGIBLE MACHINE PROPERLY GROUNDED 团 LOCAL PHONE NO. STICKER AFFIXED TO MACHINE SERVICE SECTION FUSIBLE LINK INSTALLED Ì 63 Ũ 716.88 SPENT SOLVENT MEETS ACCEPTANCE CRITERIA y 35 MACHINE INSPECTION SECTION (PLEASE CHECK APPROPRIATE BOXES ON RIGHT) **EMERGENCY CLOSING** 17 V USEPA TRANSPORTER ID NO. GENERATOR STATE ID NO. (INCLUDING PROPER SHIPPING NAME, HAZARD CLASS, AND ID.) 12. CONTAINERS NO. | TYPE TOTAL QUANTITY SK DOT NUMBER S DOT DESCRIPTION WT/VOL 630 WASTE COMBUSTIBLE LIQUID, N. O. S. MY TOTAL WAST STREAMS ARE WITHIN ONE OF THE FOLLOWING STREAMS 5 585 IPETROLEUM NAPHTHA) NA1993 PGIII OM 0001.0006.0008.0018.0035.0039.0040 ATEGORIES. B. 220 LBS./MONTH C. 2.200 LBS./MONTH INITIALS GREATER THAN 2,200 LBS./MONTH D. RT DESIGNATED FACILITY NAME AND ADDRESS USA EPA ID NO. CAT000613976 SAFETY-KLEEN CORP. STATE ID NO. 92704 CAT000613976 SANTA ANA C 0 SOUTH YALE PRODUCT SALES SECTION QUANTITY DELIVERED SALES PRODUCT NUMBER DESCRIPTION U/M LINE TOTAL GIVEN a a 0 CASH TOTAL RECEIVED APPLY PAYMENT TO: TOTAL PRODUCTS AMOUNT CHECK NUMBER TODAY'S SERVICE/SALE TOTAL SERVICE AMOUNT (FROM ABOVE) INV.# AMOUNT \$ **TOTAL DUE** PREVIOUS CREDIT CARD NO. This is to certify that the above-named materials are properly are in proper condition for transportation according to the app

IN THE EVENT OF AN EMERGENCY CALL 1-708-888-4660 (24 hours) SEE REVERSE SIDE FOR IMPORTANT INFORMATION

THUUSIRAY

GENERATOR/DESIGNATED REPRESENTATIVE SIGNATURE

SERVICE AND SALES ACKNOWLEDGEMENT

新学の おかぶ

SEE REVERSE SUE FOR IMPORTANT INFORMATION

AMOUNT \$

IN EVENT OF EMERGENCY CALL 1-708-888-4660 (24 hours)

PLEASE SEE REVERSE SIDE FOR IMPORTANT INFORMATION

Thursten)

INVOICES ARE SUBJECT TO AN INTEREST CHARGE OF THE LESSER OF 11/2% PER MONTH (18% PER ANNUM) OR THE

MAXIMUM RATE ALLOWED BY LAW ON ANY UNPAID INVOICES THAT ARE NOT PAID WITHIN 30 DAYS.

IN THE EVENT OF DEFAULT, SAFETY-KLEEN SHALL BE ENTITLED TO RECOVER COSTS OF COLLECTION INCLUDING REASONABLE ATTORNEY'S FEES.

TOARTHOO BURECHONS FOR SAFE, EFFECTIVE USE OF SAFETY-KLEEN SOLVENJAMIT DIS TYT READ BEFORE USING Elgin, Illinois 60123 SA-STV-RLEEN SOLVENT-LOU MORS O LABORD TO U.S. * 11 Safety-Kleen solvent is a high flash, hydrocarbon solvent suitable for use in degreasing applications. A. Combustibility Safety-Kleen solvent is a combustible material. That means it will burn under certain conditions. Your parts washer should <u>not</u> be installed where it can be exposed to heat, sparks or open flame; nor should there be any smoking hearby while the parts washer is in use. B. In Case of Fire Use dry chemicals, foam or carbon dioxide to extinguish flame. C. Toxicity Safety-Kleen solvent is by definition considered only slightly toxic to relatively non-toxic. Avoid inhaling or swallowing the Safety-Kleen solvent and its coming in contact with your skin, face and eyes of taken internally, splashed in your eyes, inhaled, or upon contact with your skin, face or eyes, follow the instructions below for treatment. 1. Skin contact-Remove contaminated clothing. Wash skin twice with soap and water. If irritation or pain developes or persists, consult a physician. Eyes-Wash with plenty of water. Call a physician immediately. 3. Internally-Do not induce vemiting. Call physician immediately. Guard against inhaling solvent into lungs. 4. Inhalation-Avoid Breathing solvent vapors. Adequate ventilation should be provided in any area where the Satety-Kleen parts washer is being used. clothes if your clothes become saturated with solvent change clothes immediately. Above all, do not smoke or go near an open flame or sparks while clothes are wet with solvent. II. USE OF YOUR PARTS WASHER A. Avoid leaving solvent soaked rags either in your parts washer, wadded up on workbenches or in uncovered containers. Do not put a solvent soaked rag in your pocket. It will cause a skin burn at point of contact. If you use a soaking pan, make certain that its height is less than the sink height and empty it into the sink as soon as you have finished using your parts washer. C. Do not let open pans of solvent sit either in the sink or anywhere else around your place of business. D. Safety-Kleen can not accept for reclamation materials other than the solvents originally supplied and the materials removed. from the parts cleaned. Therefore, additional solvents or other materials must not be added to the machine. You should accompande that even small amounts of low flash point materials (such as gasoline) lower the flash point of Safety-Kleen solvent substantially. Any and all solvent spills should immediately be soaked up with absorbent material, such as Safety-Kleen absorbent, and the solvent soaked material should be removed from the shop area. Contact Safety-Kleen for disposal. F. Do not remove solvent from your parts washer. -III. SAFETY-KLEEN-IMMERSION-CLEANER SOLVENT & mmersion Gleaner Solvent is a mixture of aromatic naphtha cleaning solvents and N-Methyl-2-Pyrrolidone for use in removing varnish formed on automotive parts such as carburetors, transmissions, etc. Safety-Kleen Immersion Cleaner is a combustible material. That means it will burn under certain conditions. Your Safety-Kleen Immersion Cleaner should not be installed where it can be exposed to heat, sparks or open flame; nor should there be any smoking nearby while a Safety-Kleen Immersion Cleaner unit is in use. B. In Case of Fire Use dry chemicals; foam or carbon dioxide to extinguish flame. Toxicity This solvent contains aromatic 150, N-Methyl-2-Pyrrolidone and Monoethanolamine DO NOT BREATHE MARORS! HARMFUL OR FATAL IF SWALLOWED! DO NOT INDUCE VOMITING! CALL A PHYSICIAN IMMEDIATELY. KEEP AWAY <u>FROM EYESI WASH IMMEDIATELY AND COPIOUSLY WITH RUNNING WATER, CALL A PHYSICIAN.</u> Avoid contact with skin and clothing. If solvent is inadvertently spilled on skin or clothes wash immediately with running water. Remove clothes as quickly as possible and discard. IV. SAFE USE OF YOUR SAFETY-KLEEN IMMERSION CLEANERS Keep away from heat, sparks and flame. Do not place het parts to solvent. Use only solvent provided. DO NOT ADD OTHER CHEMICALS TO THE CLEANING SOLVENT, INCLUDING BUT NOT LIMITED TO KEROSENE, FUEL OIL, GASOLINE, DETERGENTS OR CHLORINATED SOLVENTS. The use of any other solvents potentially causes a hazardous condition over which Safety-Kleen has no controt. 3. Do not smoke, drink or eat in work area. 4. Use only in well veritilated locations. Avoid repeated and/or prolonged breathing of vapors. Vapors are heavier than air and will collect in low areas. Avoid contact with eyes. Use protective eye wear such as chemical godgles 6. Avoid contact with skin. Use protective gloves and protective clothing Should you desite any further information about our solvent, our service or our company, please do not he shate to write or call Phone No. 1-800-669-5740 AND TOTAL MACHINE SERVICE AND TOTAL h imean TODAYS SEBVECE/RALE CHÈCK NUMBER 🔲 ereydous balayde a**s fo**llows RECLAMATION AGREEMENT Safety-Kleen agrees to collect too reclamation from Customer the used solvent supplied by Safety-Kleen to the machine. Collection of the used solvent shall be on a periodic basis as otherwise provided herein. Safety-Kleen shall reclaim the used with solvent for redelivery. Safety-Kleen has the capacity and is permitted to accept, store and reclaim the spent solvents AXMUM BATE ALLOWED BY LAW ON ANY UNPAID HIVORDE Safety-Kleen and Customers agree, that, this agreement is aintended to satisfy the requirements of 40 Code of Federal Regulations 262.20(e); as amended, and any state regulations which implement said provision. Customer agrees to keep this form on file for 3 years from the date of last service.

L MODAMOCOULTMATROOM/HOT BOX 3899MSS 338 389SJS